

G & R Casters and Wheels

1104 Commercial Avenue
Charlotte, NC 28205

Phone (704) 358-8787 Fax (704) 358-8788
e-mail: info@GandRcasters.com

76 Series Heavy Duty Casters

Capacity up to 4500 pounds.

Standard Features:

- All races are lubricated.
- 1" Bolt and Nut construction.
- Legs: 3/8" thick steel. **Welded inside and outside.**
- 3/4", 1", and 1-1/4" Axle with grease fitting and lock nut.
- Corrosion resistant Zinc plated parts (Wheels excluded).
- Bolt Hole Specifications: 3-3/8"X5-1/4" / 4-1/8"X6-1/8".
- Bolt Size: 1/2".

Distinct Standard Features:

- **Top plate size: 5-1/4"X7-1/4"X1/2"**
- **Grease fitting in the wheels; swivel sections and hollow axles.**
- **Top plate: S.A.E. 1045 Drop Forged Steel for durable strength.**
- **YokeBase: Machined and hardened raceways**
Notched for easy installable 4 position swivel lock.
S.A.E. 1045 Drop Forged Steel for durable strength.



Available options:

- Sealed swivel raceways.
- Quickly installable Swivel Locks.
- Thread guards on most casters.

WHEEL			Capacity in pounds	Bearing	Overall Height	Part Number	
Diameter	Width	Type				Swivel	Rigid
8"	2-1/2"	Moldon Rubber on Cast Iron	700	Roller	10-1/2"	76-MRW-0825-S	76-MRW-0825-R
		Phenolic	2000	Roller		76-PHW-0825-S	76-PHW-0825-R
		Polyurethane on Cast Iron	2000	Roller		76-PUW-0825-S	76-PUW-0825-R
		Solid Elastomer	2000	Ball		76-SEW-0825-S-B	76-SEW-0825-R-B
		Cast Iron	2500	Roller		76-CIW-0825-S	76-CIW-0825-R
8"	3"	Moldon Rubber on Cast Iron	850	Roller	10-1/2"	76-MRW-0830-S	76-MRW-0830-R
		Phenolic	2500	Roller		76-PHW-0830-S	76-PHW-0830-R
		Cast Iron	3000	Roller		76-CIW-0830-S	76-CIW-0830-R
		Polyurethane on Cast Iron	2500	Roller		76-PUW-0830-S	76-PUW-0830-R
		Solid Polyurethane	2500	Roller		76-SPW-0830-S	76-SPW-0830-R
		Solid Elastomer	2500	Ball		76-SEW-0830-S-B	76-SEW-0830-R-B
10"	3"	Moldon Rubber on Cast Iron	1000	Roller	12-1/2"	76-MRW-1030-S	76-MRW-1030-R
		Phenolic	2900	Roller		76-PHW-1030-S	76-PHW-1030-R
		Cast Iron	3000	Roller		76-CIW-1030-S	76-CIW-1030-R
		Polyurethane on Cast Iron	3000	Roller		76-PUW-1030-S	76-PUW-1030-R
		Solid Elastomer	3000	Ball		76-SEW-1030-S-B	76-SEW-1030-R-B
12"	3"	Moldon Rubber on Cast Iron	1200	Roller	15-1/2"	76-MRW-1230-S	76-MRW-1230-R
		Phenolic	3500	Roller		76-PHW-1230-S	76-PHW-1230-R
		Polyurethane on Cast Iron	3500	Roller		76-PUW-1230-S	76-PUW-1230-R
16"	3"	Moldon Rubber on Cast Iron	1500	Roller	19"	76-MRW-1630-S	76-MRW-1630-R
		Phenolic	4000	Roller		76-PHW-1630-S	76-PHW-1630-R
		Polyurethane on Cast Iron	4500	Roller		76-PUW-1630-S	76-PUW-1630-R

On the above wheels, Tapered Bearings are available.

~ Capacity ratings are based on manual operation.

G & R Casters and Wheels reserves the right to change the design, at any time, for improvement of the product without incurring any obligation to make such changes on products.

"QUALITY IS OUR TOP PRIORITY"