

G & R *Casters and Wheels*

1104 Commercial Avenue
Charlotte, NC 28205

Phone (704) 358-8787 Fax (704) 358-8788
e-mail: info@GandRcasters.com

Polyurethane on Aluminum - PAW: Flat and Balloon type treads.

- Resistance to acids and oils.
- Quiet operating movements.
- Durometer 70/80 Shore "D".
- Floor protection non-marking tread.
- High impact Polyurethane compound.
- Effortless rolling under extreme loads.
- Mechanical lock of treads to wheel center.
- Excellent performance in demanding applications.
- Sealed precision ball bearings for easy rollability.



Wheel			Bearing		Part Number	~Capacity (in pounds)
Diameter	Width	Hub Length	Type	Size		
4"	2"	2-3/16"	Ball	3/4"	PAW-0420-12	800
			Ball w/reducers	1/2"	PAW-0420-08	
5"	2"	2-3/16"	Ball	3/4"	PAW-0520-12	1000
			Ball w/reducers	1/2"	PAW-0520-08	
6"	2"	2-3/16"	Ball	3/4"	PAW-0620-12	1200
			Ball w/reducers	1/2"	PAW-0620-08	
8"	2"	2-3/16"	Ball	3/4"	PAW-0820-12	1400
			Ball w/reducers	1/2"	PAW-0820-08	

~ Capacity ratings are based on manual operation.

"QUALITY IS OUR TOP PRIORITY"