

G & R *Casters and Wheels*

1104 Commercial Avenue
Charlotte, NC 28205

Phone (704) 358-8787 Fax (704) 358-8788
e-mail: info@GandRcasters.com

Solid Elastomer (Polyurethane) Wheel - SEW:

- Less maintenance.
- Resistance to acids and oils.
- Quiet operating movements.
- Durometer 70/80 Shore "D".
- High impact Elastomer compound.
- Floor protection non-marking tread.
- Effortless rolling under extreme loads.
- Excellent for wash down environments.
- Wheels are straight sided for extra strength.
- Sealed precision ball bearings for easy rollability.



Wheel			Bearing		Part Number	~Capacity (in pounds)
Diameter	Width	Hub Length	Type	Size		
4"	2"	2-3/16"	Ball	3/4"	SEW-0420-12	700
			Ball w/reducers	1/2"	SEW-0420-08	
5"	2"	2-3/16"	Ball	3/4"	SEW-0520-12	900
			Ball w/reducers	1/2"	SEW-0520-08	
6"	2"	2-3/16"	Ball	3/4"	SEW-0620-12	1100
			Ball w/reducers	1/2"	SEW-0620-08	
8"	2"	2-3/16"	Ball	3/4"	SEW-0820-12	1500
			Ball w/reducers	1/2"	SEW-0820-08	
8"	2-1/2"	2-3/4"	Ball	1"	SEW-0825-16	1800
			Ball w/reducers	3/4"	SEW-0825-12	
8"	3"	3-1/4"	Ball	1"	SEW-0830-16	2000
			Ball w/reducers	3/4"	SEW-0830-12	
10"	2-1/2"	2-3/4"	Ball	1"	SEW-1025-16	2100
			Ball w/reducers	3/4"	SEW-1025-12	
10"	3"	3-1/4"	Ball	1"	SEW-1030-16	2300
			Ball w/reducers	3/4"	SEW-1030-12	

~ Capacity ratings are based on manual operation.

Other special sizes with ball bearings are also available. Please contact your factory rep.

"QUALITY IS OUR TOP PRIORITY"