

# **G & R** *Casters and Wheels*

1104 Commercial Avenue  
Charlotte, NC 28205

Phone (704) 358-8787 Fax (704) 358-8788  
e-mail: info@GandRcasters.com

## **Full Pneumatic Casters (FNW):**

Capacity up to 650 pounds.

### **Standard Features:**

- Rivet construction
- Legs: 1/4" thick steel.
- Top plate size: 4"X4-1/2"X1/4".
- Axle with grease fitting and lock nut.
- Corrosion resistant Zinc plated parts (Wheels excluded).
- Bolt Hole Specifications: 2-5/8"X3-5/8" / 3"X3". Bolt size: 3/8".



### **Distinct Standard Features:**

- **All raceways are heat treated.**
- **Grease fitting in wheels, swivel sections, and axles.**
- **1/4" thick steel yoke base is notched for easy installable 4 position swivel lock.**

### **Available options:**

- Sealed swivel raceways.
- Brakes
- Quickly Installable Swivel Locks.

WHEEL		Capacity in pounds	Axle Diam.	Tire Size	Bearing	Part Number	
Diameter	Height					Swivel	Rigid
8"	9-1/2"	295	1/2"	2.80/4	Ball or Roller	36-FNW-0825-S	36-FNW-0825-R
10"	11-7/8"	500	1/2"	4.10/4	Ball or Roller	36-FNW-1025-S	36-FNW-1025-R
12"	15"	650	1/2"	4.10/6	Ball or Roller	36-FNW-1215-S	36-FNW-1215-R

For ball bearing, add -BB to the end of the appropriate part number.

## **FNW Wheels**

### **Standard Features:**

- **Good shock absorption.**
- **Good floor and load protection.**
- **Three piece hub with heavy gauge steel construction.**
- **Assembled with Ball, Roller and Tapered Roller Bearings.**
- **Saw Tooth Tread Design.**



**NON-MARKING GRAY RUBBER WHEELS ARE  
AVAILABLE WITH ZINC OR BRASS PLATING HUBS.**

Diam.	Size	Capacity	Hub	Bearing	Axle Diam.	Part Number
8"	2.50-4	300	3"	Ball or Roller	1/2"	FNW-0825
10"	4.10/4	230	2-1/4" Offset	Ball	5/8"	FNW-1025-10 Offset
	4.10/4	500	3"	Ball or Roller	1/2"	FNW-1025-08
12"	4.10/6	650	3-1/4"	Ball or Roller	1/2"	FNW-1225-08

For different axle diameter than the standard, contact your factory rep.  
For bearings, add -RB or -BB to the end of the appropriate part number.

***"QUALITY IS OUR TOP PRIORITY"***